

Installation housings

Orange ECON[®] Universal 120.

With universal screw-on surface.

Flexible and quick device attachment without drilling and dowelling.



PLOPP

FX⁴ lug screws:

The fastest screw fastening for cavity wall boxes there is!



Device screws:


with plus-minus drive!

No matter which screwdriver you have at hand, it will fit!



Secure fastening

of the universal screw-on surface by means of device screws



Individual round or square installation openings

max. Ø 100 mm or max. 75x75 mm



Universal screw-on surface for the creation of individual installation openings



Plenty of space for connecting cables and accessories up to a maximum installation depth of 50 mm

Size marking on the membrane



Opening tab:

Toolless new opening technology for defined opening of the tubular membrane - guaranteed permanent air tightness!



Integrated cable retention of the NYM cables according to DIN EN 60670



Fixing of accessories with screws that reach into but not through the screw-on surface (e.g. screw with half-round head 3.5x15 mm)



Clean assembly of accessories or installation accessories

At a glance.

- With universal screw-on surface for mounting of accessories and installation accessories
- For individual round and angular installation openings
- Air-tight version with sealing membrane
- Toolless cable and conduit entry
- Integrated cable retention of NYM cables, self-locking of conduits



NEW

- Fits all electric drills with 13 mm chuck
- For cavity wall junction boxes Art. Nos. 9273-50, 9073-01/-77 as well as 9273-91/-77
- For installation housing Art. No. 9273-50



Depth	65 mm
For panel thickness	7–40 mm
Cut hole diameter	120 mm
Max. opening size Ø	100 mm
Max. opening size cornered	75x75 mm
Max. installation diameter luminaire	86 mm
For accessories with an installation depth up to max.	50 mm
Conduit entries up to Ø 25 mm	6
Cable entries 3x1.5 mm ²	6
Cable entries 3x2.5 mm ² or 5x1.5 mm ²	6
Cable entries 5x2.5 mm ² or 7x1.5 mm ²	4
Halogen-free	–
Air-tight	Yes
VDE / ÖVE	Yes / Yes
Art. No.	9273-50
Packaging inner/dispatch	- / 10

Cut hole diameter	120 mm
Cut hole depth	40 mm
Art. No.	1082-20
Packaging inner/dispatch	- / 1

Suitable tool:



Suitable accessories:



KAISER GmbH & Co. KG

Ramsloh 4 · 58579 Schalksmuehle
 GERMANY
 Phone: +49(0)23 55 8090 · Fax: +49(0)23 55 80921
 www.kaiser-elektro.de · info@kaiser-elektro.de

